

Sigen Battery

- Premium 280Ah cells with 10,000 cycles, long-lasting & reliable
- 5-layer battery safety protection redefines safety standards
- Pack-level battery optimisation, mix and match, upgrade with ease
- Higher energy density, efficient storage & compact design
- 100% depth of discharge, maximum energy utilisation



Sigen Battery

SigenStor BAT	5.0	8.0	Units
Performance Specification			
Battery type	LiFePO4		
Cell capacity	280		Ah
Cycle life 1	10000		
Total energy capacity	5.38	8.06	kWh
Usable energy capacity ²	5.2	7.8	kWh
Depth of discharge ³	100%	,	
Max. charge / discharge power	2500	4000	W
Max. charge / discharge current	7.5	12.0	А
Peak charge / discharge power (10 seconds)	3750	6000	W
General Data			
Weight	55	70	kg
Dimensions (W / H / D)	767 / 270 / 260		mm
Storage temperature range	-25 ~ 60		°C
Operating temperature range	-20 ~ 55		°C
Relative humidity range	5% ~ 95%		
Max. operating altitude	4000		m
Cooling	Natural convection		
System ingress protection rating	IP66		
Installation method	Floor standing / Wall-mounted		
Number of modules per controller	1~6		pcs
Compatible inverters	SigenStor EC series Sigen Hybrid SP2/TP2 series ⁴		
Standard Compliance			· · · · · · · · · · · · · · · · · · ·
Standard	IEC/EN 60730-1, UN 38.3, IEC/EN 62619, IEC/EN 63056, IEC/EN 62040 SigenStor BC)
Operating voltage range (Single Phase)	300 ~ 600		V
Operating voltage range (Three Phase)	600 ~ 900		V
Weight	8		kg
Dimensions (W / H / D)	765 / 109 / 260 (without decorative cover)		mm
Compatible battery system	SigenStor BAT series		
Compatible inverter	Sigen Hybrid SP2/TP2 series		
Communication	CAN		
	SigenStor EC SigenStor BAT	Sigen Hybrid SP2/TP2 SigenStor BC SigenStor BA	г

- This is provided by the battery cell manufacturer. Based on cell test condition of 25±2°C, 0.5C charge and discharge rate and SOH=60%.
- 2. Test conditions: 100% depth of discharge, 0.2C rate charge & discharge averagely at 25°C, at the beginning of life.
- Refers to the usable energy capacity.
- 4. SigenStor BC must be used if Sigen Hybrid SP2/TP2 is to be connected to the Sigen Battery.
- 5. For all standards refer to the certificates category on the Sigenergy website.

Disclaimer: The information in this file is provided on an "as is" basis. To the fullest extent permitted by law, Sigenergy Technology Co., Ltd. excludes all representations and warranties relating to this file and its contents or which is or may be provided by any affiliates or any other third party, including in relation to any inaccuracies or omissions in this file.